



TRIO PINE

APPLICABLE

- In public and residential buildings
- In heated, inhabited rooms
- In roof pitch range of 15°-90°
- Suitable on all common roofings with proper flashing

FEATURES

- Centre pivot wooden roof window
- Triple glazing
- Toughened outer glass
- Elegant bottom handle
- Two passive ventilation positions via handle
- Double gasket system between frame and sash
- Double Low-e coating
- Easy installation
- 10 year guarantee

MATERIAL | WOOD AND FINISHING

- Kiln-dried laminated pine wood
- Timber from FSC certified forests
- Fungicide protection
- Water based lacquer

COVER PARTS

- Aluminium, lacquered, grey colour (RAL 7043)

HANDLE

- Ergonomically designed moulded zinc handle, lacquered

HINGE

- Pivot hinge




AAV B1500

PANE	
Construction	4-12-3HS-12-3H
Thickness of glazing (mm)	34
Low E	■ ■
Gas	Argon
Toughened	■
U _g (W/m²K)	0.8
Total solar energy transmittance	0.55
WINDOW	
U _w (W/m²K)	1.1
Water tightness	E1350
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	33 (-1,-3) dB
COLOUR	
Natural wood	■

MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m²
C2A	55 x 78 cm	55 cm	77,8 cm	39,8 cm	64,9 cm	37,3 cm	59 cm	0.220
C4A	55 x 98 cm	55 cm	97,8 cm	39,8 cm	84,9 cm	37,3 cm	79 cm	0.295
F6A	66 x 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
M4A	78 x 98 cm	78 cm	97,8 cm	62,8 cm	84,9 cm	60,3 cm	79 cm	0.476
M6A	78 x 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597
M8A	78 x 140 cm	78 cm	139,8 cm	62,8 cm	126,9 cm	60,3 cm	121 cm	0.729
S6A	114 x 118 cm	114 cm	117,8 cm	98,8 cm	104,9 cm	96,3 cm	99 cm	0.953

FLASHING RANGE FOR DIFFERENT ROOFING MATERIALS*




SLATE
Suitable for slates and flat roofing, up to 8mm (max overall thickness is 16 mm)




TILE
Suitable for low profile tiles and profiled materials between 16-50 mm



INTERLOCKING FLAT TILE
Suitable for interlocking flat tiles between 16 and 50 mm.



UNIVERSAL
Suitable for high profiled tiles and profiled materials between 16-120 mm



STANDING SEAM
Suitable for standing seam steel sheet coverings

* Combi solutions are also available, please contact your dealer for details.

BLIND RANGE*




BLACKOUT



ROLLER



AWNING



ROLLER SHUTTER

contrio.com

*For the right product code of blinds, please take the type of blind, size of RW and colour code, e.g. DUA C2A 4219